## Impact of Vehicular Carbon Emission on Ambient Air Quality in Minna, Nigeria

## Micheal Emmanuel, Mohammed Bala Banki, Mohammed Maikudi & Santali Benjamin Aliyu

Department of Urban and Regional Planning, School of Environmental Technology Federal University of Technology, Minna<sup>1</sup> <u>mohdbanki33@gmail.com</u>

### Abstract

Movement of vehicles from one point to another is crucial to the enhancement of economic development of any society, and it leads to air pollution resulting from carbon emission. While there are substantial studies that had investigated this phenomenon, majority of it are conducted in more developed countries, and some developing countries including Nigeria. However, there is limited study on this subject in the north-central, Nigeria, which has experienced tremendous influx of different category of vehicles over the last one decade. Thus, in order to address this gap, the main objective of this paper is to assess the influence of vehicular carbon emission on ambient air quality in Minna town, with a view to ascertaining the level of carbon emission, and the variation of various emissions from different vehicular classes. For data collection, MSA Multi-Gas Detector, Smoke Meter and Handheld Gas Monitor were used to measure and determine the level of carbon emission around some roundabouts. Descriptive analysis and one sample T test were conducted. The findings of the study shows that average carbon emission around Tunga roundabout, Mobil roundabout, Kpakungu, and Obasanjo complex roundabout are 14.6ppm, 26.0ppm, 24.4ppm, and 20.8ppm respectively. All of these values are above the limit set by USEPA and WHO, and therefore classify as "highly unhealthy" limits. The study also found a highly significant variation in carbon emission around the roundabouts and various types of vehicles. The study recommends enforcement of relevant regulations on pollution control as it relates to vehicular carbon emission.

Keywords: Vehicles; Carbon emission; Pollution; Ambient air quality

### Introduction

Vehicle emissions greatly affect the air quality in many cities, especially in developing countries (MEPPRC, 2011; and Chen *et al.*, 2016). For three decades now, number of vehicles has increased rapidly worldwide, and vehicle emissions have become an important source of air pollution in most urban areas (Mayer, 1999; Panis *et al.*, 2006; as stated by Wu *et al.*, 2011). According to Shancita (2014), a vehicle emits gases, such as NOx, CO and VOCs, from its tailpipe, and even during idling state.

A considerable number of gaseous hazardous compounds are present in diesel and gasoline exhaust being emitted by vehicles (Salami, 2007). Pollutants emitted from diesel and gasoline engines of a vehicle can be divided into three major elements: NOx (nitrogen oxide), CO (Carbon monoxide) and HCs (Hydrocarbons) and PM (Particulate Matters). NOx is composed mostly of nitrogen oxide (NO) and nitrogen dioxide (NO<sub>2</sub>). In diesel exhaust, NO has a larger quantity than that of NO<sub>2</sub>, though NO<sub>2</sub> is more contagious than NO (Rodrigue, 2016).

The environmental impacts of vehicle emission arises from transportation activities as a result of increasing mobility demands for passengers and freight, which are associated with growing levels of environmental externalities (Badejo, 2011). The growth of personal and freight mobility in recent decades have expanded the role of transportation as a source of emission of pollutants and their multiple impacts on the environment (Rodrigue *et al.*, 2016).

The adverse effects of vehicular carbon emission is heavily documented in the literature, and while the dominance of this kind of study is on many cities and towns developed in countries and some developing countries, very few have been conducted on cities and towns in Nigeria. There is clearly a dearth of this nature of study in Nigeria north-central region, which is currently experiencing increasing influx of vehicles of various categories. Therefore, in addressing this gap, the main objective of this paper is to assess the influence of vehicular carbon emission on ambient air quality in Minna town with the view to ascertaining the level of carbon emission and variation of various emissions from different vehicular classes. .

### **Study Area**

Minna lies at latitude 9° 37' North and longitude 6° 33' East on a geography base

of undifferentiated Basement Complex of mainly gneiss and magmatite. The Town has a mean annual precipitation of 1300mm, taken from an exceptionally long record of 50 years. The highest mean monthly rainfall is in September with almost 3000mm. The raining season starts on average between the 11<sup>th</sup> -20<sup>th</sup> April, and lasts between 190 and 200 days. Temperature rarely falls below 22° C. The peaks are 40° C (February-March) and 35° C (November-December). Minna City is both the administrative headquarters of State and Chanchaga Local Niger Government Area. The City has 2017 estimated population of 489,351. It covers approximately 1000Ha (Maxlock, 1980). According to the Niger State Board of Internal Revenue (BIR) (2017), a total of 13,729 vehicles were registered in Minna from September, 2013-December 2016. This includes motorcycles, tricycles, cars, buses, light and heavy trucks. Figure 1.1 shows street guide map of Minna showing major roundabouts, while figure 1.2 shows selected traffic light points.



Figure 1.1: Street Guide Map of Minna Showing Major Roundabouts



Figure 1.2: Street Guide Map of Minna Showing Major Junctions

## Literature Review Transportation and Greenhouse Gas Emission

Transportation is the major contributor of air pollution accounting for over 80 percent of total air pollutants (UN Habitat's State of the World Cities 2008/2009). According USEPA (2014), greenhouse gas to emissions from transportation accounted for about 26 percent of total U.S. greenhouse gas emissions, making it the largest second contributor of U.S. greenhouse gas emissions after the electricity sector. US Environmental Protection Agency (EPA) (2014) indicates that the transportation sector includes the movement of people and goods by cars, trucks, trains, ships, airplanes, and other Majority of greenhouse gas vehicles. emissions from transportation are carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>), sulphur dioxide (SO<sub>2</sub>) and nitrogen oxide (NOx) emissions resulting from the combustion of petroleum-based products, such as gasoline, internal combustion engines. Fossil fuel usage is the primary source of  $CO_2$ . The transportation sector directly accounted for about 28 percent of total U.S. GHG emissions in 2006, making

it the second largest source of GHG emissions after electricity generation (UN Habitat's State of World Cities 2008/2009).

NESREA (2014) noted that air pollution can occur inside homes, schools, and offices; in cities; and across continents. Major air pollutants which can be experienced at any given time include: Oxides of Nitrogen (NO<sub>X</sub>), Oxides of Sulphur (SO<sub>X</sub>), Carbon monoxide (CO), Ozone  $(O_3)$ , Hydrogen sulphide  $(H_2S)$ , Methane (CH<sub>4</sub>), Total Non-methane Hydrocarbon (TNMHC). Particulate Matter (PM) and Volatile Organic Chemicals/Compounds (VOCs). Vlieger et  $al_{..}(2010)$  stated that the largest sources of transportation GHGs in 2006 were passenger cars (34%) and light duty trucks, which include sport utility vehicles, pickup trucks, and minivans (28%). Together with motorcycles, these light-duty vehicles made up about 63% of transportation GHG emissions. The next largest sources were freight trucks (20%) and commercial aircraft (7%), along with other non-road sources, which combined totalled about 7%. These figures include direct emissions from fossil fuel combustion, as well as

Impact of Vehicular Carbon Emission on Ambient Air Quality in Minna, Nigeria

HFC emissions from mobile air conditioners and refrigerated transport allocated to these vehicle types.

In Nigeria, little attention is given to pollution caused by mobile transportation which is a source of air pollution according to Abam (2009) and Nwachukwu (2012). The situation of increased pollution from mobile transportation source is as a result of increase in private and public vehicle ownership, thus resulting in high road congestion in cities and towns in Nigeria. and increase in the concentration of pollutants in the air, resulting in increased health risk of human population (Odotong, 2015). Studies conducted in Kaduna and Abuja cities show higher values of CO<sub>2</sub>concentration in heavily congested areas: 1840ppm was recorded for Sabo in Kaduna city, 1780ppm for Stadium roundabout in Kaduna city, and 1530ppm for A.Y.A in Abuja city, 1160ppm for Asokoro in Abuja city (Hassan et al., 2012).

## Materials and Methods Instrument for Data Collection:

The following instruments were used: Digital Camera, Hand held GPS (Garmin, etrex10 model), and the MSA Altair 5X Multi-gas Detector. The MSA Altair 5X Multi-gas Detector of version SW 1.27.06.50 is a portable hand held device used to measure the concentration of gases in the environment. The device monitors gases in ambient air, and is available with a maximum of four sensors, which can display readings for five separate gases (one Dual Toxic Sensor provides both CO and H<sub>2</sub>S sensing capabilities in a single sensor), Oxygen (O<sub>2</sub>) and 2 combustible gases including Pentane. For the purpose of this research, 7 of out of the 13 roundabouts in Minna were considered for the study. They are: Tunga roundabout, Kpakungu roundabout, Mobile roundabout, Obasanjo Complex roundabout, Maitumbi roundabout, Minna City-Gate roundabout, and Paiko roundabout. The factors considered for selection include; volume of traffic generated, hierarchy of the road, activities along/ adjacent the route, and busy nature of the roads. Also, 3 of the major traffic junctions out of the 7 junctions identified were selected for the research due to the traffic generated and clustered nature of the roads. The ambient air monitoring procedure was adopted using the description made by Harrop (2002) and Robert (2004).

During the atmospheric measurement, air samples were measured in part per million (ppm) at a height of 1 metres above the ground level at each of the graded distances of 1 metres from the road. An approximate distance of 0.27 metres from the tail pipe of idling vehicles was adopted for the second strategy. This measurement was done at the windward direction. Carbon emission levels at the roundabouts were taken at three distinct period of the day; 8am-10am, 12pm-2pm, and 4pm-6pm and the collection of air samples was measured on site. Second by second measurement with an interval of 2-3 seconds was adopted. The second by second emission data provides a better method for the development of models for estimating vehicular emission. A GPS receiver was used to record the positional status of all the major roundabouts and junctions. The collected data was analysed using SPSS 22, where descriptive analysis and one sample T test was conducted. The results of analysis are presented in charts and tables.

## **Results and Discussion**

# Average Level of Carbon Emission at Selected Roundabouts in Minna

The average daily carbon emission at the selected roundabouts in Minna ranges from 14.6ppm at Tunga roundabout to as high as 26.0ppm at Mobile roundabout. This is presented in Table 4.1. The result shows that the average carbon emission around selected roundabouts in the city is 19.7ppm. Mobile roundabout recorded the highest average carbon emission of 26.0ppm, followed by Kpakungu and Obasanjo Complex with 24.4ppm and 20.8ppm values respectively. These three (3) Roundabouts recorded higher carbon

Environmental Technology & Science Journal Vol. 8 No. 2 December 2017.

emission than Minna City-Gate roundabout. The average carbon emission at Minna City-Gate roundabout is 18.3ppm, Paiko roundabout recorded 17.6ppm, Maitumbi roundabout recorded 16.3ppm, while the lowest value (14.6ppm) was recorded at Tunga roundabout.

The United States Environmental Protection Agency (USEPA, 2015)identified six levels of carbon emission, and their health implication. Going by their standard, six (6) out of the seven (7) selected roundabouts recorded carbon emission that falls under the very unhealthy level (see table 4.1). Carbon emission value recorded at Tunga roundabout is unhealthy for sensitive group of people (Asthmatic). Therefore, majority of the roundabouts in Minna experiences high concentration of CO<sub>2</sub> that is harmful to man. Excessive concentration of  $CO_2$  in the atmosphere according Bascom, et al (1996) can reduce the oxygen carrying capacity of blood which might affect the sensitive organs of the human body such as the heart and brain. Similarly, USEPA (2015) reveals that acute exposure to vehicles' emission over a period of time reduces lung function. Furthermore, Balogun (2015) noted that vehicle that produces excessive smoke (smoke could be gray, blue, white or black depending on the engine's state) on the road can affect visibility, thereby causing Road Traffic Crash (RTC).



Figure 4.1: Vehicular Emission around Selected Roundabouts in Minna

Roundabout Daily Average Carbon Emission		Remark		
Location				
Tunga	14.6	Unhealthy for sensitive groups		
Kpakungu	24.4	Highly Unhealthy		
Mobile	26.0	Highly Unhealthy		
Obasanjo	20.8	Highly Unhealthy		
Maitumbi	16.3	Highly Unhealthy		
City Gate	18.3	Highly Unhealthy		
Paiko	17.6	Highly Unhealthy		
City Mean	19.7	Highly Unhealthy		

Table 4.1 Daily Average Carbon Emissions at Selected Roundabouts in Minna

Note that: 0-4.4ppmc = Good, 4.5-9.4ppmc = Moderate, 9.5-12.4ppm = Unhealthy for Sensitive groups,

12.5-15.4ppm = Unhealthy, 15.5-30.4ppm = Highly unhealthy, 30.5-50.4ppm = Hazardous (USEPA, 2015)

## Variation in Volume of Carbon Emission Recorded At the Selected Roundabouts in Minna

Table 4.2 shows the variation in volume of carbon emission recorded at the selected roundabouts in Minna using one sample T Test. The one sample T test recorded a t value of 14.266 and a P-value of 0.000. Since the p-value is less than 0.001 at 95% confidence level, it therefore implies that there is a significant variation in the level of carbon emission recorded at the selected roundabouts in Minna.

## Amount of Carbon Concentration Emitted by Vehicles in Minna

The carbon emission from nine major categories of vehicles was examined at idling state using the MSA Multi-gas Detector. The average volume of carbon emitted by vehicles at idling state is presented in Figure 4.2. The result shows that the average volume of carbon emitted by tanker/trailer, lorry/truck motorcycle, tricycle, private car at idling state are 153.43ppm, 232.13ppm, 236.12ppm, Table 4.2. One-Sample Test

289.39ppm, 343.17ppm respectively. Furthermore, the volume of emission recorded from luxury bus at idling state is Omni 388.64ppm, bus recorded 442.53ppm, pick-up recorded van 520.23ppm, while commercial cars recorded 627.04ppm. The result shows that the volume of carbon emission from vehicles is not a function of its size, but other numerous factors not considered in this study.

#### Variation in Volume of Carbon Concentration Emitted by Various Categories of Vehicles in Minna

Table 4.3 shows the variation in volume of carbon concentration emitted by various types of vehicles in Minna using one sample T Test. The one sample T test recorded a t value of 7.100 and a P-value of 0.000. Since the p-value is less than 0.001 at 95% confidence level, it therefore implies that there is a significant variation in the concentration of carbon emitted by various categories of vehicles in Minna.

Table 4.2. One-bample Test							
	Test Value $= 0$						
				Mean	95% Confider the Dif	nce Interval of ference	
	t	df	Sig. (2-tailed)	Difference	Lower	Upper	
Carbon Emission	14.266	7	.000	19.71250	16.4450	22.9800	



Figure 4.2: Carbon Concentration Emitted by Vehicles in Minna Table 4.3. One-Sample Test

	Test Value – 0
	1  cst  value = 0
-	

				Moon	95% Confidence Interval of the Difference	
	t	df	Sig. (2-tailed)	Difference	Lower	Upper
Emission	7.100	8	.000	359.18667	242.5343	475.8391

#### **Conclusion and Recommendations**

This study has shown that the amount of carbon emission (particularly CO viii. concentration) by vehicles around the roundabouts and some junctions in Minna are above the recommended limits. It therefore confirmed the findings of Ndoke et al (2000) and Nwachukwu et al(2012) that vehicular emission contributes to the concentration CO in the atmosphere with its impact on the environment.

Based on the findings of the research, the following recommendations are suggested:

- i. The Vehicle Inspection Office (VIO) should be strengthened by the State to enforce Excessive Smoke Violation (ESV) among the motorists.
- ii. The use of intelligent traffic system should be introduced in Minna in order to reduce the idling time of vehicles in major Junctions.
- iii. The Motor park at Mobile roundabout should be relocated to reduce both human and vehicular traffic around the Roundabout.
- iv. The Obasanjo Shopping Complex is the main economic hub around the Obasanjo Complex roundabout. The State should provide multi-level parking lots based on Private Public Partnership (PPP) within the trekking distance of five (5) minutes, or 25 to 30 metres away from the Shopping Complex in order to reduce the rate of vehicular movement around the axis.
- v. Residential buildings around the major Roundabouts should be relocated because of the carbon exposure, while residential development should be discouraged.
- vi. There should be enforcement of setbacks for other buildings and informal economic activities at the major Roundabouts.
- vii. The use of non-motorised transport system which is pollution free

should be encouraged to replace the vehicles driven by fossil fuel.

- ii. There is need for integrated approach to tackle air pollution relating to vehicular movement and climate change, thereby making use of the most costeffective measures. A good example is vehicle maintenance, use of catalytic converter as pollution control device, and planting of trees or plants around the traffic hotspots to trap carbon.
- ix. There should be awareness creation on the impact of carbon emission on major traffic hotspots in Minna. This will include production and distribution of information and communication materials on air pollution control in public places.
- x. There should be enforcement of relevant of regulations on motor vehicle emission and pollution control as it relates to carbon emission.
- xi. There is the need to address the transport demand issues through the use of intra mass transit system and discourage private vehicular use in the Town. This will reduce carbon emission and improve energy efficiency.
- xii. Ring roads and Bye-passes should be constructed to avoid thoroughfare for vehicles that do not have business in the city of Minna.

### References

- Abam, F and Magbabeola T (2009): Vehicular Emission and Air Quality Standard in Nigeria; European Journal of Scientific Research, Vol.34 No.4
- Agbola, T., Egunjobi, L., Olatubara, C.O., Ola Yusug D.O and Alabi M (2003). Research Methods: A Practical Guide. Murlab Educational Services Marina, Lagos. Pp 255-264.
- Badejo, B. A. (2011). Transportation: Removing the Clogs to Nigeria's

Impact of Vehicular Carbon Emission on Ambient Air Quality in Minna, Nigeria

Development. Anchorage Press and Publishers, Lagos. Pp 67-89

- Balogun, S., A (2015). Introduction to Road Traffic Crash Investigation. A paper delivered during SRC-CRC Course at FRSC Academy Udi, Enugu.
- Balogun, S., A (2011). Road Safety Practice in Nigeria; BOAAS Resource Publishers Nig. Ltd, Abuja, 2<sup>nd</sup> Edition.
- Bascom, R., Bromberg, P., Costa, D., Delvin, R., Dockery, D., Frampton, M., Lambert, W., Samet, J., Speizer, F. and Utel, M. (1996), "Health effects of outdoor air pollution: Parts I and II", American Journal of Respiratory Critical Care Medicine, Vol. 153, pp. 477-498
- Chandioa, I. A., Brohi, K. M., & Memon, M. A. (2010). Managing road traffic noise pollution, through sustainable planning approach. *International Journal of Chemical and Environmental Engineering*, 1(2).
- Chen, J., Li, C., Ristovski, Z., Milic, A., Gu, Y., Islam, M. S., & Guo, H. (2016). A review of biomass burning: Emissions and impacts on air quality, health and climate in China. *Science* of the Total Environment.
- Environmental Protection and Disaster Risk Reduction (2012). A school guide, UN/SDR Africa Educational Series, 4, 3.
- Faiz, A. (1993). Automotive Emissions in Developing Countries- Relative Implication for Global Warming, Acidification and Urban Air Quality. Transport Research A, 27, 167-186.
- Frank, M (2009): Control of Motor emission-the US Experience. Critical Review on Environmental Control. Available at http://dx.doi.org/10.1080/1064338919 9.388423
- Good, P., Gosling, S. N., Bernie, D., Caesar, J., Warrens, R., Arnell, N.
  W., & Lowe, J. A. (2010). An updated review of developments in climate science research since the IPCC Fourth Assessment Report.

- Han, X. and Naeher, L. P. (2006), "A review of traffic-related air pollution exposure assessment studies in the developing world", <u>ENVIRONMENTAL</u> <u>INTERNATIONAL</u>, Vol. 32, pp. 106 – 120.
- Harrop D.O (2002). Air Quality Assessment and Management . An online publication.
- Hassan, S. M., & Abdullahi, M. E. (2012). Evaluation of Pollutants in Ambient Air: A Case Study of Abuja-Nigeria. Int. J. Sci. and Research, 2(12), 1-9.
- Kolawole, P. (2012). Global Warming and Food Engineering Emissions.
- Mac Kinnon, M., Shaffer, B., Carreras-Sospedra, M., Dabdub, D., Samuelsen, G. S., & Brouwer, J. (2016). Air quality impacts of fuel cell electric hydrogen vehicles with high levels of renewable power generation. *International Journal of Hydrogen Energy*, 41(38), 16592-16603.
- Mastrandrea, M. D., Heller, N. E., Root, T. L., & Schneider, S. H. (2010). Bridging the gap: linking climateimpacts research with adaptation planning and management. *Climatic Change*, *100*(1), 87-101.
- Maxlock (1980). Minna Master Plan
- MEPPRC (2014). The Interaction Between China's Economic Growth, Energy Production and Consumption and the related Air Emission During 2000-2011. Ecological Indicator, Vol 46
- Ndoke P.N. and Jimoh O.D. (2000). Impact of Traffic Emission on Air Quality in a Developing City of Nigeria. Leonardo Electronic Journal of Practices and Technologies. 6 (9): 88-92.
- NESREA (2014). Air Pollution Control: A Strategy in Environmental Protection. Module 6. A NESREA Publications
- Nigeria Highway Code (2016). Federal Road Safety Commission, 4<sup>th</sup> Edition, Detail Work Publishers Ltd, 110-120.
- Nwachukwu, A. N., Chukwuocha, E. O., & Igbudu, O. (2012). A survey on the effects of air pollution on diseases of

Environmental Technology & Science Journal Vol. 8 No. 2 December 2017.

the people of Rivers State, Nigeria. African Journal of Environmental Science and Technology, 6(10), 371-379.

- Okunola, O. J., Uzairu, A., Gimba, C. E., & Ndukwe, G. I. (2012). Assessment of gaseous pollutants along high traffic roads in kano, Nigeria. *International Journal of Environment and Sustainability*, 1(1).
- Olagunju, K (2011): Road Sense, 1st Edition, Veragap Publishers Nigeria Limited.
- Qu, L., Li, M., Chen, D., Lu, K., Jin, T., & Xu, X. (2015). Multivariate analysis between driving condition and vehicle emission for light duty gasoline vehicles during rush hours. *Atmospheric Environment*, *110*, 103-110.
- Robert, B (2004). The Vehicle Emission and Performance Monitoring System: Analysis of Tailpipe Emission and Vehicle's Performance. Centre for Transport Studies, Department of Civil and Environmental Engineering, Imperial College London, London SWT2AZ
- Rodrigue, J. P., Comtois, C., & Slack, B. (2016). *The geography of transport systems*. Taylor & Francis.
- Salami, K., A (2007): Emission Control Technology by Automotive Industry: Trend and Challenges; Inaugural Lecture Series 10, Federal University of Technology, Minna, Nigeria.
- Shancita, I., Masjuki, H. H., Kalam, M. A., Fattah, I. R., Rashed, M. M., & Rashedul, H. K. (2014). A review on idling reduction strategies to improve fuel economy and reduce exhaust

emissions of transport vehicles. *Energy conversion and management*, 88, 794-807.

- Stephens, R. D., & Cadle, S. H. (1991). Remote sensing measurements of carbon monoxide emissions from onroad vehicles. *Journal of the Air & Waste Management Association*, 41(1), 39-46.
- Udotong, J. I. R. (2015). Air quality Assessment at Traffic Control Points in Uyo Metropolis. Nigeria– International Journal of Engineering and Technical Research (IJETR), 3, 325-331.
- United States Environmental Protection Agency (2014). Global Greenhouse Gas Emissions. Data. Available at https://www.epa.gov/ghgemissions/gl obal-greenhouse-gas-emissions-data
- United States Environmental Protection Agency (2015). US Greeenhouse Gas Inventory Report; 1990-2014. Published April, 2015
- UN Habitat's State of the World Cities (2008/2009) Harmonious Cities: Earthscan Publishers. London. Sterling.
- Vlieger, J (2010). Impact of Eco-driving on Passenger Use and Greenhouse Gas Emission. Technical Document, California Environmental Protection Agency, Air Resource Board.
- Wu, J., Xie L., Li Q and Chen, D (2011). Association Control for vehicular Wi-Fi Access: Pursuing Efficiency and Fairness. IEEE Transaction on parallel and Distribution System. Vol 22, No 6, 2011